

Bright

VM 30n



Carrozzeria: acciaio inox
Pompa di vuoto: 106 mc/h
Dimensioni: mm 1141x889x1069h
Dimensioni camera a vuoto: mm 1027x680x200h
Peso: 291 kg
Tensione: 400V 50/60Hz 3ph PPE
Potenza max assorbita: 2500 W
Dimensione max busta: variabile

Carrosserie: acier inoxydable
Pompe à vide: 106 mc/h
Dimensions: mm 1141x889x1069h
Chambre à vide: mm 1027x680x200h
Poids: 291 kg
Voltage: 400V 50/60Hz 3ph PPE
Puissance max absorbée: 2500 W
Dimension max du sac: variable

Bodywork: stainless steel
Vacuum pump: 106 mc/h
Size: mm 1141x889x1069h
Chamber size: mm 1027x680x200h
Weight: 291 kg
Power grid voltage: 400V 50/60Hz 3ph PPE
Max power absorption: 2500 W
Max bag size: variable

Carrocería: acero inoxidable
Bomba de vacío: 106 mc/h
Medidas: mm 1141x889x1069h
Cámara de vacío: mm 1027x680x200h
Peso: 291 kg
Tensión: 400V 50/60Hz 3ph PPE
Potencia máx: 2500 W
Tamaño máx de bolsa: variable



KIT PREMIUM

SACCHETTI SOTTOVUOTO LISCI
SMOOTH VACUUM BAGS

SACCHETTI PER COTTURA
COOKING VACUUM BAGS

dim/size(mm)	qty x box	dim/size(mm)	qty x box
150x200	200	200x300	100
200x300	200	250x350	100
250x350	100		
300x400	100		
350x450	100		
400x500	100		

STANDARD
Barre saldanti - Sealing beams
950 mm
950 mm

STANDARD
Barre saldanti - Sealing beams
555 mm
555 mm

STANDARD
Barre saldanti - Sealing beams
505 mm
900 mm

Icon	Italian	French	English	Spanish
	Sistema disaerazione	Deaeration programs	Programmes de désaération	Programas de desaireación
	Programmi di vuoto preimpostati	Vacuum preset programs	Vides programmes	Programas vacío preestablecidos
	Pannello digitale	Digital command panel	Panneau digital	Mandos digitales
	Sistema sensoriale di vuoto	Vacuum sensor	Système de mise sous vide sensoriel	Sistema de vacío con sensor
	Doppia resistenza*	Double resistance*	Double résistance*	Doble soldadura*
	Taglio sfrido*	Cut of seal*	Coupe sachets*	Recorte sobrante de bolsa*
	Ugello per contenitori	Nozzle for jars	Embout pour récipients	Boquilla para contenedores externos
	Gas	Gas	Gaz	Gas
	USB	USB	USB	USB
	H2out	H2out	H2out	H2out
	Softair	Softair	Softair	Softair
	Kit Premium	Kit Premium	Kit Premium	Kit Premium

* non è possibile avere questi 2 optional assieme
 * please note, if you have the cut of seal you cannot have the double resistance.

* Sur les machines à cloche, il n'est pas possible d'avoir simultanément le coupe sachet et la double résistance.
 * no se podrá contar con estos 2 opcionales juntos



ORVED S.P.A. con Socio Unico
 Via dell'Artigianato, 30 - 30024 Musile di Piave (VE) - ITALIA
 tel: +39 0421 54387 - fax: +39 0421 332295
 www.orved.it - orved@orved.it